


PVC ASTM SCH80


PVC SCHEDULE 80 FITTINGS

Couplings




Nom. Pipe Size	Max. O.D. Dim. M1	S801U		
		L1	C	Approx. Wt.(lb)
1/2	30.16	48.42	22.23	0.051
3/4	35.72	54.77	25.80	0.080
1	44.45	61.91	28.97	0.110
1 1/4	53.18	67.47	32.15	0.160
1 1/2	60.33	74.22	35.32	0.220
2	73.42	80.57	38.10	0.310
2 1/2	88.90	93.27	43.66	0.690
3	105.97	102.00	48.02	1.000
4	132.95	121.05	57.94	1.690
6	198.44	160.34	76.20	3.586
8	257.18	238.13	114.30	7.815
10	301.63	366.71	152.40	16.447
12	358.78	415.93	158.75	25.050
14	393.70	533.40	215.90	38.000

Female Couplings




Nom. Pipe Size	Max. O.D. Dim. M2	S801U-1		
		L2	T	Approx. Wt.(lb)
1/2	33.34	40.88	17.07	0.080
3/4	38.10	44.85	18.65	0.092
1	46.04	54.37	23.02	0.140
1 1/4	55.56	57.15	26.99	0.200
1 1/2	63.50	57.15	27.78	0.250
2	76.20	57.15	28.58	0.340
2 1/2	92.08	79.38	37.31	0.690
3	109.54	80.96	38.89	0.940
4	138.91	84.93	39.69	1.380

Male Adapters



Nom. Pipe Size	Max. O.D. Dim. M	S802U			
		C	S	L	Approx. Wt.(lb)
1/2	30.16	22.62	19.45	47.63	0.047
3/4	35.72	26.19	21.03	52.78	0.063
1	43.66	28.97	25.00	59.93	0.102

Female Adapters



Nom. Pipe Size	Max. O.D. Dim. M	S803U			
		L	C	T	Approx. Wt.(lb)
1/2 x 1/2	30.16	47.63	22.62	17.07	0.047
1/2 x 3/4	30.16	52.78	26.19	18.65	0.063
3/4 x 3/4	35.72	59.93	28.97	23.02	0.102